

Compact 12 camera flight unit

Power Consumption	10 kVA on 3 x 16A Schuko connector
Dimensions	Packed :3 x Case H:142 W:56 D:89 - 1 x DESK Case H:99 W:166 D:84 Work Area : 6 x 4 m

Equipement Specifications

Cameras	Up to 12 Sony High- or Standard Definition Cameras BVP950;BVP9500;BVP500;BVP550;HDC950;HDC1550
Switcher	GVG Kayak 100, 1 ME, HD/SD Switchable 24 inputs;12outputs;6 ch Ramrecorder, DVE with Glow/Defocus, Chroma Keyers
Matrix Patch	Leitch Panacea 16 x 8 HD/SD router with Clean switch ADC, 196 Patch Points
Monitorwall	16 HD/SD sources on Zandar Predator multiviewer on 42" plasma 14" Sony CRT grade A monitor
Rec / Play	Up to 12 VTR : Digital Betacam, HD cam, Betacam SX, Up to 4 HDR : EVS XT2, GVG Turbo, Tektronix PDR100, 2 x VHS/DVD combo
Glue	Snell & Wilcox 6200, Barco Folsom Image Pro HD, Leitch, Axon, As requested
Mixer	Yamaha DM1000 20 Mic/line inputs, 4 Omni inputs
Patch	Ghielmetti, 288 Patch Points
Monitoring	Genelec Active Near Field Monitors
Rec / Play	CD, Minidisk, DAT, Hard Disk
Inserts	Dbmax, As requested
Intercom	Clearcom MMX 24 : 16 x 16 3 internal ICS stations 2 external ICS stations 2 x 2 wire interface 2 x 4 wire interface
ISDN/PSTN	Telos ISDN Codec EELA Telephone Hybrids
Wireless	Motorola GP340 - Rieface Radiocom BTR 700 Icom Receivers